

U.S. ARMY CORPS OF ENGINEERS

BKM

| DEPTH, FEET | SAMPLE NO. | PEN./TORVANE SPT.-BLOW COUNT | GENERAL INFORMATION | | | | |
|-------------|------------|---------------------------------|---|---------------|--------------|-----------------------------|--------------------------------------|
| | | | BORING NO. | DATE: BEGIN | PAGE | THIN WALLED TUBE | COMPLETE |
| | | | 91- 37 | 03-11-91 | 111 | Thin Walled Tube | |
| | | | 146446 | | | | |
| | | | PROJECT CHANNEL TO VICTORIA | | | <input type="checkbox"/> 3" | <input type="checkbox"/> 6" |
| | | | LOCATION VICTORIA CHANNEL | | | | |
| | | | ELEVATION OF HOLE | | | | |
| | | | MANUFACTURER'S DESIGNATION OF DRILL RIG F-36 | | | | |
| | | | GROUNDWATER: DEPTH 1 1/2 ft., ELEV. ft., at end of Drilling | | | | |
| | | | WEATHER PARTLY CLOUDY & WINDY | | | | |
| | | | DRILLER ROBERT TANKERSLEY | | | | LOGGER John D. [Signature] |
| | | | COLOR | MATERIAL TYPE | CONSISTENCY | SECONDARY CONSTITUENTS | STRUCTURAL FEATURES AND COMMENTS |
| 0 | | | | | | | |
| | 1 | 1.5 | GRAY | CLAY | STIFF | | -w/ ROOTS 0'-2' |
| | 2 | 1.75 | " | " | " | | *YTAN |
| 5 | 3 | 1.75 | " | " | " | | |
| | 4 | 1.25 | " | " | " | | |
| | 5 | 0.5 | " | " | MEDIUM STIFF | | |
| 10 | 6 | 0.5 | " | " | " | | |
| | 7 | 0.25 | " | " | SOFT | | -w/SAND SEAMS 12'-16' |
| 15 | 8 | 0.25 | " | " | " | | |
| | 9 | 0.25 | GRAY | CLAY | SOFT | VERY SANDY | -w/SHELL FRAGMENTS 16-20 1/2 |
| | 10 | 0.25 | " | " | " | " | |
| 20 | 11 | 1/1 | GRAY | SAND | Very Loose | SILTY | FINE -w/SHELL FRAGMENTS BELOW 20 1/2 |
| 25 | 12 | 1/1 | " | " | " | " | |
| 30 | 13 | 1/1 | " | " | " | " | |
| 35 | 14 | 1/1 | " | " | " | " | |