



Aptim Environmental & Infrastructure, LLC

6401 Congress Avenue, Suite 140

Boca Raton, Florida 33487

Phone # 1-561-391-8102

Legend for Geotechnical Data

Grain Size Scale for Sediments

Unified Soil Classification System (USCS) (ASTM D2487/2488)		APTIM Standard Sieve Stack		
		Sieve Number	Size (phi)	Size (mm)
Gravel	Coarse Gravel	3/4	-4.25	19.03
	Fine Gravel	5/8	-4.00	16.00
		7/16	-3.50	11.20
		5/16	-3.00	8.00
		3 1/2	-2.50	5.60
		4	-2.25	4.75
Sand	Coarse Sand	5	-2.00	4.00
		7	-1.50	2.80
		10	-1.00	2.00
	Medium Sand	14	-0.50	1.40
		18	0.00	1.00
		25	0.50	0.71
		35	1.00	0.50
	Fine Sand	45	1.50	0.36
		60	2.00	0.25
		80	2.50	0.18
		120	3.00	0.13
		170	3.50	0.09
		200	3.75	0.08
Fines	Silt/Clay	230	4.00	0.06

Proportional Definition of Descriptive Terms

<u>Descriptive Term</u>	<u>Range of Proportions</u>
Sandy, gravelly, etc.	35 % to 50 %
Some	20 % to 35 %
Little	10 % to 20 %
Trace	1 % to 10 %

Consistency of Cohesive Soils

Description	Consistency Index	Approximate Undrained Shear Strength (kPa)	Field Identification
Hard		Over 300	Indented with difficulty by thumbnail, brittle.
Very Stiff	>1	150-300	Readily indented by thumbnail, still very tough.
Stiff	0.75-1	75-150	Readily indented by thumb but penetrated only with difficulty. Cannot be moulded in the fingers.
Firm	0.5-0.75	40-75	Can be penetrated several centimeters by thumb with moderate effort and moulded in fingers by strong pressure.
Soft	<0.5	20-40	Easily penetrated several centimeters by thumb, easily moulded.
Very Soft		Less than 20	Easily penetrated several centimeters by fist, exudes between fingers when squeezed in fist.


Source: *Engineering Properties of Soils and Rocks, Fourth Edition by Fred G. Bell*


USCS Classifications

Refers to the Army Corps of Engineers Unified Soils Classification System. Class types are defined primarily by grain size, sorting and percent of material passing the #200 sieve. Classification of materials on the core logs based on visual field examinations are identified on the core logs under the Classification of Materials Description. Classifications based on laboratory sieve analyses are identified on the core logs in the Legend and under Remarks.

GW		Well graded gravels or gravel-sand mixtures, little or no fines	ML		Inorganic silts and very fine sands, rock flour, sandy silts or clayey silts with slight plasticity
GP		Poorly graded gravels or gravel-sand mixtures, w/ little or no fines	MH		Inorganic silts, micaceous or diatomaceous fine sandy or silty soil, elastic silts
GM		Silty gravels, gravel-sand-silt mixtures	OL		Organic silts and organic silt-clays of low plasticity
GC		Clayey gravels, gravel-sand-clay mixtures	OH		Organic clays of medium to high plasticity, organic silts
SW		Well graded sands or gravelly sands, little or no fines	CL		Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays
SP		Poorly graded sands or gravelly sands, little or no fines	CH		Inorganic clays of high plasticity, fat clays
SM		Silty sands, sand-silt mixtures	PT		Peat and other highly organic soils
SC		Clayey sands, sand-clay mixtures	SP-SM		Poorly-graded silty sand
SW-SM		Well-graded silty sand	SM-SC		Silty clayey sand
GW-GM		Well-graded silty gravel	ML-CL		Inorganic silty lean clay
GM-GC		Clayey silty gravel			

Note: Information is after ACOE Atlantic Division Manual # 1110-1-1 titled *Engineering and Design Geotechnical Manual for Surface and Subsurface Investigations*

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1 SHEETS	
1. PROJECT TX GLO Region 1 Recon Geotechnical Sand Search Jefferson, Chambers, Galveston and Brazoria Co. 				9. SIZE AND TYPE OF BIT 3.0 In.			
2. BORING DESIGNATION TXGLO1-VC-23-054				10. COORDINATE SYSTEM/DATUM Texas State Plane South		HORIZONTAL NAD 1983	
3. DRILLING AGENCY APTIM				11. MANUFACTURER'S DESIGNATION OF DRILL APTIM SEAS VC-700 Vibracore		VERTICAL NAVD88	
4. NAME OF DRILLER APTIM				12. TOTAL SAMPLES			
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				13. TOTAL NUMBER CORE BOXES		14. ELEVATION GROUND WATER	
6. THICKNESS OF OVERBURDEN 0.0 Ft.				15. DATE BORING		STARTED 10-12-23 COMPLETED 10-12-23	
7. DEPTH DRILLED INTO ROCK 0.0 Ft.				16. ELEVATION TOP OF BORING -37.8 Ft.			
8. TOTAL DEPTH OF BORING 19.2 Ft.				17. TOTAL RECOVERY FOR BORING 15.2 Ft.			
				18. SIGNATURE AND TITLE OF INSPECTOR BF			
ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS The USCS classification system defines silt as the percent passing the No.200 (0.075 mm) sieve	
-37.8	0.0						
-39.2	1.4		LEAN CLAY, very soft, trace sand, fine grained, quartz, sand distributed in laminae, dark gray (5Y-4/1), (CL).		T1	Sample #T1, Depth = 0.6' Ave. Field Vane (tsf): 0.00	
-40.4	2.6		LEAN CLAY, very soft, little sand, fine grained, quartz, trace shell hash, sand distributed in laminae, shell hash distributed in sand laminae, dark gray (5Y-4/1), (CL).		T2	Sample #T2, Depth = 2.2' Ave. Field Vane (tsf): 0.00	
-49.8	12.0		FAT CLAY, soft, little sand, fine grained, quartz, sand distributed in laminae, dark greenish gray (10Y-4/1), (CH).		T3	Sample #T3, Depth = 7.0' Ave. Field Vane (tsf): 0.03	
-53.0	15.2		FAT CLAY, stiff, little organics, organics distributed in laminae, Bit sample from 14.8' to 15.2', dark gray (N-4/0), (CH).		T4	Sample #T4, Depth = 13.7' Ave. Field Vane (tsf): 0.10	
-57.0	19.2		No recovery.				
			End of Boring				



Texas General
Land Office

Texas GLO
Region 1
Geotechnical
Reconnaissance
Survey

TXGLO1-VC-23-054

Date Collected: 10/12/23
Top Elev. (ft NAVD88): -37.8
Bottom Elev. (ft NAVD88): -53.0
Core Length (ft): 15.2



6401 Congress Avenue, Suite 140
Boca Raton, FL 33487
www.aptim.com
(561)391-8102



Mini Vane Shear Test Results

CORE ID	SAMPLE DEPTH (ft)	TORVANE (kg/cm ²)	TORVANE (tsf)	TORVANE (kpa)	DESCRIPTION ¹
TXGLO1-VC-23-048	2.2	2.8	0.28	269.68	Very Stiff
	4.8	1.5	0.15	147.10	Stiff
TXGLO1-VC-23-049	3.0	1.5	0.15	147.10	Stiff
	4.0	5.0	0.51	490.33	Hard
	5.1	1.5	0.15	147.10	Stiff
	9.4	6.5	0.67	637.43	Hard
	15.5	9.5	0.97	931.63	Hard
TXGLO1-VC-23-050	4.8	1.0	0.10	98.07	Stiff
	8.1	1.5	0.15	147.10	Stiff
	10.4	2.0	0.20	196.13	Very Stiff
	11.7	2.0	0.20	196.13	Very Stiff
	14.7	2.5	0.26	245.17	Very Stiff
TXGLO1-VC-23-051	1.0	1.0	0.10	98.07	Stiff
	1.8	1.5	0.15	147.10	Stiff
	3.1	3.5	0.36	343.23	Hard
	6.4	10.0	1.02	980.67	Hard
	11.0	10.0	1.02	980.67	Hard
TXGLO1-VC-23-052	1.0	0.0	0.00	0.00	Very Soft
	3.0	0.0	0.00	0.00	Very Soft
	11.5	7.5	0.77	735.50	Hard
	14.6	8.0	0.82	784.53	Hard
	16.0	9.0	0.92	882.60	Hard
TXGLO1-VC-23-053	0.5	0.0	0.00	0.00	Very Soft
	2.2	0.5	0.05	49.03	Firm
	18.0	2.5	0.26	245.17	Very Stiff
TXGLO1-VC-23-054	0.6	0.0	0.00	0.00	Very Soft
	2.2	0.0	0.00	0.00	Very Soft
	7.0	0.3	0.03	24.52	Soft
	13.7	1.0	0.10	98.07	Stiff
TXGLO1-VC-23-055	0.3	0.5	0.05	49.03	Firm
	1.6	1.0	0.10	98.07	Stiff
	3.1	1.0	0.10	98.07	Stiff
	8.9	4.0	0.41	392.27	Hard
	14.1	4.8	0.49	465.82	Hard
TXGLO1-VC-23-056	No Torvane Conducted				
TXGLO1-VC-23-057	6.4	1.5	0.15	147.10	Stiff
TXGLO1-VC-23-058	0.8	0.5	0.05	49.03	Firm
	4.2	1.0	0.10	98.07	Stiff
	12.9	1.5	0.15	147.10	Stiff
	15.5	2.0	0.20	196.13	Very Stiff