



Aptim Environmental & Infrastructure, LLC

6401 Congress Avenue, Suite 140

Boca Raton, Florida 33487

Phone # 1-561-391-8102

Legend for Geotechnical Data

Grain Size Scale for Sediments

Unified Soil Classification System (USCS) (ASTM D2487/2488)		APTIM Standard Sieve Stack		
		Sieve Number	Size (phi)	Size (mm)
Gravel	Coarse Gravel	3/4	-4.25	19.03
	Fine Gravel	5/8	-4.00	16.00
		7/16	-3.50	11.20
		5/16	-3.00	8.00
		3 1/2	-2.50	5.60
		4	-2.25	4.75
Sand	Coarse Sand	5	-2.00	4.00
		7	-1.50	2.80
		10	-1.00	2.00
	Medium Sand	14	-0.50	1.40
		18	0.00	1.00
		25	0.50	0.71
		35	1.00	0.50
	Fine Sand	45	1.50	0.36
		60	2.00	0.25
		80	2.50	0.18
		120	3.00	0.13
		170	3.50	0.09
		200	3.75	0.08
Fines	Silt/Clay	230	4.00	0.06

Proportional Definition of Descriptive Terms

<u>Descriptive Term</u>	<u>Range of Proportions</u>
Sandy, gravelly, etc.	35 % to 50 %
Some	20 % to 35 %
Little	10 % to 20 %
Trace	1 % to 10 %






















Consistency of Cohesive Soils

Description	Consistency Index	Approximate Undrained Shear Strength (kPa)	Field Identification
Hard		Over 300	Indented with difficulty by thumbnail, brittle.
Very Stiff	>1	150-300	Readily indented by thumbnail, still very tough.
Stiff	0.75-1	75-150	Readily indented by thumb but penetrated only with difficulty. Cannot be moulded in the fingers.
Firm	0.5-0.75	40-75	Can be penetrated several centimeters by thumb with moderate effort and moulded in fingers by strong pressure.
Soft	<0.5	20-40	Easily penetrated several centimeters by thumb, easily moulded.
Very Soft		Less than 20	Easily penetrated several centimeters by fist, exudes between fingers when squeezed in fist.


Source: *Engineering Properties of Soils and Rocks, Fourth Edition by Fred G. Bell*

USCS Classifications


Refers to the Army Corps of Engineers Unified Soils Classification System. Class types are defined primarily by grain size, sorting and percent of material passing the #200 sieve. Classification of materials on the core logs based on visual field examinations are identified on the core logs under the Classification of Materials Description. Classifications based on laboratory sieve analyses are identified on the core logs in the Legend and under Remarks.

GW		Well graded gravels or gravel-sand mixtures, little or no fines	ML		Inorganic silts and very fine sands, rock flour, sandy silts or clayey silts with slight plasticity
GP		Poorly graded gravels or gravel-sand mixtures, w/ little or no fines	MH		Inorganic silts, micaceous or diatomaceous fine sandy or silty soil, elastic silts
GM		Silty gravels, gravel-sand-silt mixtures	OL		Organic silts and organic silt-clays of low plasticity
GC		Clayey gravels, gravel-sand-clay mixtures	OH		Organic clays of medium to high plasticity, organic silts
SW		Well graded sands or gravelly sands, little or no fines	CL		Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays
SP		Poorly graded sands or gravelly sands, little or no fines	CH		Inorganic clays of high plasticity, fat clays
SM		Silty sands, sand-silt mixtures	PT		Peat and other highly organic soils
SC		Clayey sands, sand-clay mixtures	SP-SM		Poorly-graded silty sand
SW-SM		Well-graded silty sand	SM-SC		Silty clayey sand
GW-GM		Well-graded silty gravel	ML-CL		Inorganic silty lean clay
GM-GC		Clayey silty gravel			

Note: Information is after ACOE Atlantic Division Manual # 1110-1-1 titled *Engineering and Design Geotechnical Manual for Surface and Subsurface Investigations*

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1 SHEETS	
1. PROJECT TX GLO Region 1 Recon Geotechnical Sand Search Jefferson, Chambers, Galveston and Brazoria Co. 				9. SIZE AND TYPE OF BIT 3.0 In.			
2. BORING DESIGNATION TXGLO1-VC-23-055				10. COORDINATE SYSTEM/DATUM Texas State Plane South		HORIZONTAL NAD 1983	
LOCATION COORDINATES (ft) X = 3,367,947 Y = 13,696,549				11. MANUFACTURER'S DESIGNATION OF DRILL <input type="checkbox"/> AUTO HAMMER APTIM SEAS VC-700 Vibracore <input type="checkbox"/> MANUAL HAMMER			
3. DRILLING AGENCY APTIM				12. TOTAL SAMPLES 0		DISTURBED 5	
4. NAME OF DRILLER APTIM				13. TOTAL NUMBER CORE BOXES			
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				14. ELEVATION GROUND WATER			
DEG. FROM VERTICAL				15. DATE BORING 10-12-23			
BEARING				COMPLETED 10-12-23			
6. THICKNESS OF OVERBURDEN 0.0 Ft.				16. ELEVATION TOP OF BORING -38.4 Ft.			
7. DEPTH DRILLED INTO ROCK 0.0 Ft.				17. TOTAL RECOVERY FOR BORING 16.6 Ft.			
8. TOTAL DEPTH OF BORING 19.2 Ft.				18. SIGNATURE AND TITLE OF INSPECTOR KS			
ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS The USCS classification system defines silt as the percent passing the No.200 (0.075 mm) sieve	
-38.4	0.0						
-39.1	0.7		FAT CLAY, firm, some sand, fine grained, quartz, trace silt, 0.25" sand pocket @ 0.3', very dark greenish gray (10Y-3/1), (CH).		T1	Sample #T1, Depth = 0.3' Ave. Field Vane (tsf): 0.05	
-40.3	1.9		Sandy FAT CLAY, stiff, trace shell hash, trace silt, sand component is fine grained quartz, 2.0" sand pocket @ 0.7', (1.5" x 2.0") sand pocket @ 1.3', dark greenish gray (10Y-4/1), (CH).		T2	Sample #T2, Depth = 1.6' Ave. Field Vane (tsf): 0.10	
-44.7	6.3		Sandy FAT CLAY, stiff, trace shell hash, trace silt, lenticular bedding throughout layer, flaser bedding between 2.6' & 3.0' and between 4.3' & 4.6', dark greenish gray (10Y-4/1), (CH).		T3	Sample #T3, Depth = 3.1' Ave. Field Vane (tsf): 0.10	
-48.9	10.5		FAT CLAY, hard, little silt, trace sand, fine grained, quartz, trace shell hash, trace whole shell, lenticular bedding throughout layer, 1.0" shell hash pocket with whole bivalves @ 6.5', 2.0" shell hash pocket with whole bivalves @ 6.8', shell hash lamina @ 9.6', dark gray (N-4/0), (CH).		T4	Sample #T4, Depth = 8.9' Ave. Field Vane (tsf): 0.41	
-55.0	16.6		FAT CLAY, hard, trace shell hash, Bit sample from 16.3' to 16.6', dark greenish gray (10GY-4/1), (CH).		T5	Sample #T5, Depth = 14.1' Ave. Field Vane (tsf): 0.49	
-57.6	19.2		No recovery.				
			End of Boring				

REGION 1 RECON GEOTECH GP-1 3/25/24



Texas General
Land Office

Texas GLO
Region 1
Geotechnical
Reconnaissance
Survey

TXGLO1-VC-23-055

Date Collected: 10/12/23
Top Elev. (ft NAVD88): -38.4
Bottom Elev. (ft NAVD88): -55.0
Core Length (ft): 16.6



6401 Congress Avenue, Suite 140
Boca Raton, FL 33487
www.aptim.com
(561)391-8102



Mini Vane Shear Test Results

CORE ID	SAMPLE DEPTH (ft)	TORVANE (kg/cm ²)	TORVANE (tsf)	TORVANE (kpa)	DESCRIPTION ¹
TXGLO1-VC-23-048	2.2	2.8	0.28	269.68	Very Stiff
	4.8	1.5	0.15	147.10	Stiff
TXGLO1-VC-23-049	3.0	1.5	0.15	147.10	Stiff
	4.0	5.0	0.51	490.33	Hard
	5.1	1.5	0.15	147.10	Stiff
	9.4	6.5	0.67	637.43	Hard
	15.5	9.5	0.97	931.63	Hard
TXGLO1-VC-23-050	4.8	1.0	0.10	98.07	Stiff
	8.1	1.5	0.15	147.10	Stiff
	10.4	2.0	0.20	196.13	Very Stiff
	11.7	2.0	0.20	196.13	Very Stiff
	14.7	2.5	0.26	245.17	Very Stiff
TXGLO1-VC-23-051	1.0	1.0	0.10	98.07	Stiff
	1.8	1.5	0.15	147.10	Stiff
	3.1	3.5	0.36	343.23	Hard
	6.4	10.0	1.02	980.67	Hard
	11.0	10.0	1.02	980.67	Hard
TXGLO1-VC-23-052	1.0	0.0	0.00	0.00	Very Soft
	3.0	0.0	0.00	0.00	Very Soft
	11.5	7.5	0.77	735.50	Hard
	14.6	8.0	0.82	784.53	Hard
	16.0	9.0	0.92	882.60	Hard
TXGLO1-VC-23-053	0.5	0.0	0.00	0.00	Very Soft
	2.2	0.5	0.05	49.03	Firm
	18.0	2.5	0.26	245.17	Very Stiff
TXGLO1-VC-23-054	0.6	0.0	0.00	0.00	Very Soft
	2.2	0.0	0.00	0.00	Very Soft
	7.0	0.3	0.03	24.52	Soft
	13.7	1.0	0.10	98.07	Stiff
TXGLO1-VC-23-055	0.3	0.5	0.05	49.03	Firm
	1.6	1.0	0.10	98.07	Stiff
	3.1	1.0	0.10	98.07	Stiff
	8.9	4.0	0.41	392.27	Hard
	14.1	4.8	0.49	465.82	Hard
TXGLO1-VC-23-056	No Torvane Conducted				
TXGLO1-VC-23-057	6.4	1.5	0.15	147.10	Stiff
TXGLO1-VC-23-058	0.8	0.5	0.05	49.03	Firm
	4.2	1.0	0.10	98.07	Stiff
	12.9	1.5	0.15	147.10	Stiff
	15.5	2.0	0.20	196.13	Very Stiff