

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
BORING NO. <u>E3-03</u> DATE: BEGIN <u>10-16-02</u> PAGE <u>111</u>					JOB NO. <u>1140127279</u> COMPLETE <u>10-16-02</u> Thin Walled Tube				
PROJECT <u>Lost Lake Placement Area</u>					LOCATION <u>X=3,243,582.4518, Y=725,741.2426</u>				
ELEVATION OF HOLE <u>22.93</u>					MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u>				
GROUNDWATER: DEPTH <u>3</u> ft., ELEV. _____ ft., at end of Drilling					WEATHER <u>SUNNY</u>				
DRILLER <u>Dempsey Locant</u> LOGGER <u>John A. Gentry</u>									
0	J 2	1.50	GRAY	CLAY	STIFF			-W/ROOTS + SAND SMS 0-9"	
	J 3		GRAY	SAND	V. LOOSE	SILT			
	J 4	0.00	GRAY	SAND	V. LOOSE	SILT			
5	J 5		GRAY	CLAY	V. SOFT			-W/SAND SMS	
	X 6	2.33	GRAY	SAND	LOOSE				
10	X 7	3.35	GRAY	SAND	LOOSE				
	8	0.00	GRAY	CLAY	V. SOFT			-W/SAND SMS	
15	9	0.75	GRAY	CLAY	M. STIFF			-W/SAND SMS	
	10	0.50	GRAY	CLAY	M. STIFF			-W/SAND SMS	
	11	0.50	GRAY	CLAY	M. STIFF			-W/SAND SMS	
20	12	0.00	DARK GRAY	CLAY	V. SOFT			X DARK GRAY CLAY @ 20	
	13	0.00	DARK GRAY	CLAY	V. SOFT			-W/HIDRO CARBON OVAR 20-24	
25	14	0.00	DARK GRAY	CLAY	V. SOFT				
30								J = JAR SAMPLE	
35									