

LOG OF BORING

Project : MTBE Improvement Areas-Tenneco Natural Gas Liquids Corp., La Porte, Texas
 Client : M.W. Kellogg Company
 Houston, Texas
 Boring No. : 8-102
 File No. : 90-0422
 Date : 7-11-90
 Elevation : +21 ft.
 Dry Augered 0 to 25 ft. Water at 24.0 ft.; Caving at ft.
 Wash Bored 25 to 60 ft. Water at 7.60 ft. after 25 minutes

ELEV	SOIL SYMBOLS SAMPLER SYMBOLS AND FIELD TEST DATA	Description	Wc (%)	Dens. (pcf)	Qu. or UU (tsf)	Str (%)	LL	PI	#200 (%)
DEPTH									
0	4.50	Very stiff dark gray CLAY (CH) -w/roots to 2'	22						
	3.75		23						
	2.00	-stiff w/calcareous nodules below 4'	26	100	1.86	12			
5	1.25	-firm, tan & light gray w/ferrous nodules below 6'	24						
	3.25	-very stiff below 8'							
10	2.75	-stiff below 10'							
	2.25								
15									
	2.75								
20									
	2.75	-w/silt layers & calcareous nodules @ 23'	24						
25									
	3.50	-very stiff below 28'							
30									

Bottom @ 60'

LOG OF BORING

Project : MTBE Improvement Areas-Tenneco Natural Gas Liquids Corp., La Porte, Texas
 Client : M.W. Kellogg Company
 Houston, Texas
 Boring No. : B-102
 File No. : 90-0422
 Date : 7-11-90
 Elevation : +21 ft.
 Dry Augered 0 to 25 ft. Water at 24.0 ft.; Caving at ft.
 Wash Bored 25 to 60 ft. Water at 7.60 ft. after 25 minutes

ELEV	SOIL SYMBOLS SAMPLER SYMBOLS AND FIELD TEST DATA	Description	Wc (%)	Dens. (pcf)	Qu or UU (tsf)	Str (%)	LL	PI	#200 (%)
DEPTH									
30		Very stiff tan & light gray CLAY (CH)							
35									
40		-red & light gray w/sand pockets below 38'	22	99					
45		-brown & gray below 43'	31	93	2.05 (23)	2			
50		-tan & light gray w/silt pockets & layers @ 48'	20						
55									
60									

Bottom @ 60'