

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET	SAMPLE NO.	PEN./TORVANE SPT.-BLOW COUNT	BORING NO. <u>WY-01</u> DATE: BEGIN <u>9-26-02</u> PAGE <u>111</u> JOB NO. <u>1140127279</u> COMPLETE <u>9-26-02</u> Thin Walled Tube PROJECT <u>Lost Lake Placement Area</u> ☒ 3" ☐ 6" LOCATION <u>X=3237251.44, Y=725680.97</u> ELEVATION OF HOLE _____ MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u> GROUNDWATER: DEPTH <u>12</u> ft., ELEV. _____ ft., at end of Drilling WEATHER <u>PARTLY CLOUDY</u> DRILLER <u>Dempsey Gearen</u> LOGGER <u>John A. Gentry</u>				
			COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
0	1	1.00	GRAY + BROWN	CLAY	STIFF		-w/SHELL FRAG.
	2	1.50	REDDISH BROWN + GRAY	CLAY	STIFF		-w/SHELL FRAG Calc Nods
5	3	1.25	REDDISH BROWN + GRAY	CLAY	STIFF		
	4	1.00	REDDISH BROWN + GRAY	CLAY	STIFF		
10	5	1.00	REDDISH BROWN + GRAY	CLAY	STIFF		
	6	1.00	REDDISH BROWN + GRAY	CLAY	STIFF		
	J 7		GRAY	SAND	V. LOOSE	SILT	
15	J 8	0.00	DARK GRAY	CLAY	V. SOFT		SAMPLE Buldge on extrusion
	9	0.00	GRAY + DK GRAY	CLAY	V. SOFT		
	10	0.00	Gray	CLAY	V. SOFT		
20	11	0.00	DK GRAY + GRAY	CLAY	V. SOFT		
	12	0.00	DK GRAY + GRAY	CLAY	V. SOFT		
25	13	0.00	DK GRAY + GRAY	CLAY	V. SOFT		
30							
35							

J = SAND SAMPLE