

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE	SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	BORING NO. <u>E3-15</u> DATE: BEGIN <u>10-17-02</u> PAGE <u>111</u>					
						JOB NO. <u>1140127279</u> COMPLETE <u>10-17-02</u> Thin Walled Tube					
						PROJECT <u>Lost Lake Placement Area</u> ☒ 3" ☐ 6"					
						LOCATION <u>X=3,242,993.1397 Y=725,628.4987</u>					
						ELEVATION OF HOLE <u>19.89</u>					
						MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u>					
						GROUNDWATER: DEPTH <u>2</u> ft., ELEV. _____ ft., at end of Drilling					
						WEATHER <u>SUNNY</u>					
						DRILLER <u>Dempsey Casareen</u> LOGGER <u>John A. Gentry</u>					
		COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS					
0	J	1	GRAY + LT BROWN	SAND	V. LOOSE		- W/ROOTS & CLAY SMS				
		2	BROWN + GRAY	CLAY	V. SOFT						
	X	3	GRAY + BROWN	SILT	LOOSE						
		4	DARK GRAY	CLAY	V. SOFT		- W/HYDROCARBON O OAR 4-6				
5		5	GRAY + BROWN	CLAY	V. SOFT		- W/ROOTS & SAND SMS				
		6	BROWN + GRAY	CLAY	V. SOFT						
10	J	7	GRAY + BROWN	SAND	V. LOOSE						
		8	DARK GRAY + GRAY	CLAY	V. SOFT		- W/HYDROCARBON O OAR 12-14				
15	J	9	GRAY	SAND	LOOSE	SILT					
	X	10	GRAY	SAND	LOOSE	SILT					
		11	DARK GRAY + GRAY	CLAY	V. SOFT		* DARK GRAY CLAY @ 18' - W/STL & SMS @ 18' - W/HYDROCARBON O OAR 18-24				
20		12	DARK GRAY	CLAY	V. SOFT						
		13	DARK GRAY + GRAY	CLAY	V. SOFT						
25	J = JAR SAMPLE										
30											
35											