

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
BORING NO. <u>E3-06</u> DATE: BEGIN <u>10-16-02</u> PAGE <u>1/1</u>										
JOB NO. <u>1140127279</u> COMPLETE <u>10-16-02</u> Thin Walled Tube										
PROJECT <u>Lost Lake Placement Area</u> ☒ 3" ☐ 6"										
LOCATION <u>X=3,243,435.1238, Y=725,713.0566</u>										
ELEVATION OF HOLE <u>22.96</u>										
MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u>										
GROUNDWATER: DEPTH <u>3</u> ft., ELEV. _____ ft., at end of Drilling										
WEATHER <u>SUNNY</u>										
DRILLER <u>Dempsey Garen</u> LOGGER <u>John A. Gentry</u>										
0		J 1	0.50			GRAY L.BROWN	CLAY	M. STIFF	SILT	-w/ 50 SMS & ROOTS 3 sa pkts, clay pkts, sample fell apart.
		J 2				GRAY BROWN	SAND	V. LOOSE	SILT	
-5		X 3	1.1			DARK GRAY	SAND	V. LOOSE	SILT	
		X 4	4.6			GRAY	SAND	M. DENSE	SILT	
		X 5	3.23			GRAY	SAND	LOOSE	SILT	-w/ CLAY SMS.
-10		X 6	3.4			GRAY	SAND	LOOSE	SILT	-w/ CLAY SMS
		J 7				GRAY	SAND	LOOSE		-w/ SAND SMS
		8	0.50			GRAY BROWN	CLAY	M. STIFF		
-15		J 9				GRAY	SAND	M. DENSE		
		X 10	8.10			GRAY	SAND	M. DENSE		
		X 11	7.13			GRAY	SAND	M. DENSE		
-20		12	0.00			DARK GRAY	CLAY	V. SOFT		DARK GRAY CLAY ~ 20' -w/ HYDROCARBON OADR 20-22'
		13	0.00			DARK GRAY	CLAY	V. SOFT		
-25		14	0.00			DARK GRAY GRAY	CLAY	V. SOFT		
-30										
-35										