Port Aransas
Corpus Christi
Waterway

LOG OF BORING NO. 35T-57 (82)

TYPE: 3" Shelby Tube

LOCATION:

DEPTH FT.	SYMBOL	SAMPLES	DESCRIPTION OF MATERIAL (SURF. EL.)	BLOWS PER FT.	UNIT DRY WT. LBS./CU.FT.	POCKET PENETROMETER TONS / SQ. FT. (0.5 1.0 1.5 2.0 2.5 3.0) / PLASTIC LIMIT — WATER CONTENT, % (10 20 30 40 50 60) — LIQUID LIMIT	ELEVATION FT
			WATER 40.0' Tide +2.5 @ 7:00 A.M.				
40	C L		DARK GRAY SANDY CLAY V/SOFT 0-16-84			Gray Sandy Clay (CL) 18 V/Soft	178.2
45	S C		WHITE CLAYEY SAND Dense 0-72-28	24		White Clayey Sand (SC) 22 ~~Dense~~ V/Stiff	
50	C L		LIGHT GRAY SANDY CLAY w/CAL. NODS V/STIFF W/LARGE SANDSTONE GRAVEL 2-20-78			Gray Sandy Clay (CL) 23 V/Stiff w/S.S. & Cal Nods	
			D.C. TAN SAND			Tan Silty Gravelly Sand (SM) 5 V/Dense, w/Cal Nods	
	S M		SILTY GRAVELLY SAND Cal. nods, black quartzite V/DENSE 34-34-37	1			
55							

COMPLETION DEPTH
DATE

DEPTH TO WATER
IN BORING

DATE

SWN 266(C)
22 AUG 62