

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	PEN./TORVANE SPT.-BLOW COUNT	COLOR	MATERIAL TYPE	CONSIS- TENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
BORING NO. <u>E3-20</u> DATE: BEGIN <u>10-17-02</u> PAGE <u>111</u> JOB NO. <u>1140127279</u> COMPLETE <u>10-17-02</u> Thin Walled Tube PROJECT <u>Lost Lake Placement Area</u> ☒ 3" ☐ 6" LOCATION <u>X=3242.747.5929 Y=725.5815221</u> ELEVATION OF HOLE <u>18.59</u> MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u> GROUNDWATER: DEPTH <u>2</u> ft., ELEV. _____ ft., at end of Drilling WEATHER <u>Sunny</u> DRILLER <u>Dempsey Gecaren</u> LOGGER <u>John A. Gentry</u>								
0		1	0.00	BROWN	CLAY	V. SOFT		-w/ROOTS
		2	0.00	BROWN	CLAY	V. SOFT		
		3	0.00	DARK GRAY	CLAY	V. SOFT		-w/HYDRO CARBON O.DAR 2-4
5		4	0.00	BROWN +GRAY	CLAY	V. SOFT		
		5	0.00	BROWN +GRAY	CLAY	V. SOFT		-w/SAND ON BOTTOM 8
		J 6		GRAY	SILT	V. LOOSE	SAND	
10		7	0.00	OK GRAY BROWN	CLAY	V. SOFT		
		J 8		GRAY	SAND	M. DENSE	SILT	
15		X 9	24	GRAY	SAND	M. DENSE	SILT	
		J 10	0.00	DARK GRAY	CLAY	V. SOFT		DARK GRAY CLAY on 16 -w/HYDRO CARBON O.DAR 16-22 SAMPLE BULDC 16-20
		J 11	0.00	DARK GRAY	CLAY	V. SOFT		
20		J 12	0.00	DARK GRAY + GRAY	CLAY	V. SOFT		
25								J = JAR SAMPLE
30								
35								