

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	BORING NO. <u>E2-19</u> DATE: BEGIN <u>10-17-02</u> PAGE <u>111</u> JOB NO. <u>1140127279</u> COMPLETE <u>10-17-02</u> Thin Walled Tube PROJECT <u>Lost Lake Placement Area</u> ☒ 3" ☐ 6" LOCATION <u>X=3,242,796.7023</u> <u>Y=725,590.9174</u> ELEVATION OF HOLE <u>18.77</u> MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000, Marsh Buggy</u> GROUNDWATER: DEPTH <u>2</u> ft., ELEV. _____ ft., at end of Drilling WEATHER <u>Sunny</u> DRILLER <u>Dempsey Gearen</u> LOGGER <u>John A. Gentry</u>				
						COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
0			1	0.00		BROWN GRAY	CLAY	V. SOFT		-W/ROOTS & SILT SMS
			2	0.00		BROWN DARK GRAY	CLAY	V. SOFT		-W/HYDROCARBON O.DAR 2-6
-5		J	3	0.00		BROWN DARK GRAY	CLAY	V. SOFT		SAMPLE BULGE
			4	0.00		BROWN GRAY	CLAY	V. SOFT		
		X	5	233		GRAY	SAND	LOOSE	SILT	
-10		X	6	454		GRAY	SAND	LOOSE	SILT	
		X	7	223		GRAY	SAND	LOOSE	SILT	
-15		X	8	112		GRAY	SAND	V. LOOSE	SILT	
			9	0.00		DARK GRAY	CLAY	V. SOFT		DARK GRAY CLAY W/16 W/HYDROCARBON O.DAR 16-22
			10	0.00		DARK GRAY	CLAY	V. SOFT		
-20			11	0.00		DARK GRAY	CLAY	V. SOFT		
-25										J = JAR SAMPLE
-30										
-35										