

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE	SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	BORING NO. <u>E1-13</u> DATE: BEGIN <u>10-21-02</u> PAGE <u>1/1</u> JOB NO. <u>1140127279</u> COMPLETE <u>10-21-02</u> Thin Walled Tube PROJECT <u>Lost Lake placement Area</u> ☒ 3" ☐ 6" LOCATION <u>X=3,243 218.5530</u> <u>Y=727,789.9600</u> ELEVATION OF HOLE <u>17.59</u> MANUFACTURER'S DESIGNATION OF DRILL RIG <u>Pontoon mounted - Marsh Buggy</u> GROUNDWATER: DEPTH <u>8"</u> ft., ELEV. _____ ft., at end of Drilling WEATHER <u>CLOUDY</u> DRILLER <u>Dempsey Green</u> LOGGER <u>John A. Gentry</u>				
						COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
0			1	0.00		BROWN + GRAY	CLAY	V. SOFT		W/ROOTS
			2			GRAY + LT BROWN	SAND	V. LOOSE		W/ROOTS
5			3	1		GRAY + LT BROWN	SAND	V. LOOSE		
			4	0.00		BROWN + GRAY	CLAY	V. SOFT		W/ SILT SMS
			5	0.00		BROWN + GRAY	CLAY	V. SOFT		
10			6	0.00		BROWN + GRAY	CLAY	V. SOFT		
			7	0.00		DARK GRAY	CLAY	V. SOFT		DARK GRAY CLAY 12' - W/ HYDROCARBON 00AR 12-18'
15			8	0.00		DARK GRAY	CLAY	V. SOFT		
			9	0.00		DARK GRAY	CLAY	V. SOFT		
20										
25										
30										
35										