

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	BORING NO. <u>EI-01</u>	DATE: BEGIN <u>10-18-02</u>	PAGE <u>1/1</u>		
						JOB NO. <u>1140127279</u>	COMPLETE <u>10-18-02</u>	Thin Walled Tube ☒ 3" ☐ 6"		
						PROJECT <u>Lost Lake Placement Area</u>				
						LOCATION <u>X=3,243,791.137, Y=727,610.6626</u>				
						ELEVATION OF HOLE _____				
						MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u>				
						GROUNDWATER: DEPTH _____ ft., ELEV. _____ ft., at end of Drilling				
						WEATHER <u>PARTLY CLOUDY</u>				
						DRILLER <u>Dempsey Gacaren</u>	LOGGER <u>John A. Gentry</u>			
						COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
0		1	1.00			REDDISH BROWN + GRAY	CLAY	STIFF		-W/ROOTS
		2	0.00			GRAY	CLAY	USOFT		
5		3	2.00			GRAY	CLAY	USOFT		
		4	1.00			GRAY	CLAY	STIFF		
		5	0.75			GRAY	CLAY	M. STIFF		
10		6	0.00			GRAY + BROWN	CLAY	USOFT		-W/ SAND SMS
		7	1.00			REDDISH BROWN + GRAY	CLAY	STIFF		
15		8	0.75			REDDISH BROWN + GRAY	CLAY	M. STIFF		
		9	0.25			BROWN + GRAY	CLAY	SOFT		
		10	0.00			DARK GRAY	CLAY	USOFT		X DARK GRAY CLAY W/ 18" W/ HYDROCARBON OIL
20		11	0.25			DARK GRAY + GRAY	CLAY	SOFT		
		12	0.25			DARK GRAY	CLAY	SOFT		
25										
30										
35										