



Quaternary Resource Investigations, LLC  
 13588 Florida Blvd  
 Baton Rouge, LA 70819  
 Telephone: 225-292-1400  
 Fax: 225-292-1404

**BORING NUMBER 13-B113**

CLIENT \_\_\_\_\_ PROJECT NAME Peggy Lake Placement Area  
 PROJECT NUMBER W912HY-13-D-0001; Task Order 0002 PROJECT LOCATION La Porte, Texas  
 DATE STARTED 4/12/2013 8:30:00 AM COMPLETED 4/12/2013 6:00:00 PM GROUND ELEVATION 18.7482 ft HOLE SIZE 8.25 inches  
 DRILLING CONTRACTOR Quaternary Resource Investigations, LLC NORTHING 13836225.36 ft EASTING 3215845.977 ft  
 DRILLING METHOD Hollow Stem Auger DRILLING RIG MAKE/MODEL Mobile B57 on Gemco Articulated Platform  
 LOGGED BY Terri Russin TOTAL DEPTH 60 ft GROUND WATER LEVEL \_\_\_\_\_  
 WEATHER sunny, warm, 60s - 70s, breezy AT TIME OF DRILLING 8.00 ft / Elev 10.75 ft 4/12/2013 9:23:00 AM

COPY OF PEGG - PEGGY LAKE TEMPLATE.GDT - 10/2/13 10:39 - C:\DOCUMENTS AND SETTINGS\RL

COPY OF PEGG - PEGGY LAKE TEMPLATE.GDT - 10/2/13 10:39 - C:\DOCUMENTS AND SETTINGS\RL

COPY OF PEGG

GRAPHIC LOG	USCS SYMBOL	MATERIAL DESCRIPTION	DEPTH (ft)	SAMPLE TYPE	RECOVERY (in)	SPT BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	FIELD TORVANE (tsf)	DRY UNIT WT. (pcf)	MOISTURE CONTENT (%)	ATTERBERG LIMITS			MINUS #200 SIEVE CONTENT (%)	COMPRESSIVE STRENGTH (tsf)	FAILURE STRAIN (%)	CONFINING PRESSURE (psi)
											LIQUID LIMIT	PLASTIC LIMIT	PLASTICITY INDEX				
	CL	Silty CLAY, light brown, moist, medium to high plasticity, with grass, rootlets and caliche	0	ST	9		3.2			30							
				ST	12		2.25		101	24	64	20	44		2.71	9.2	0
	SP	SAND, light brown fine grained, moist, no plasticity	5	SS	22	10-11-9-10 (20)	3.75			5				10			
		wet, very fine grained, laminated	10	SS	12	5-12-11-9 (23)	1.25			15				14			
	CH	CLAY, light brown to yellow orange (orange color increasing with depth), moist, high plasticity	15	SS	12	1-2-3-5 (5)	1.25			43							
		with caliche, increasing with depth		ST	16		1.5		101	21	80	23	57	86	1.23	5.3	0
	CH		20	ST	20		0	5.7		34							
				ST	21		0.8		98	26	76	21	55	85			
	CH	CLAY, dark gray, moist, high plasticity, soft, hydrocarbon odor	25	ST	16		1.75			29							
				ST	21		2.75			35							
	CH			ST	14		0.75/1.75			26							
				ST	22		1.8/0	-/3.2	59	67	119	30	89	99	0.43	1.5	7.2
	CL	Silty CLAY, olive gray, moist, low plasticity, with shells (increasing with depth) and caliche		ST	21		0/0	2.2/1.7		81							
				ST	19		0/0	1.4/3.2	87	37							
		about 1' of olive gray CLAY, moist, medium to high plasticity, with shells and caliche	35														

(Continued Next Page)



Quaternary Resource Investigations, LLC  
 13588 Florida Blvd  
 Baton Rouge, LA 70819  
 Telephone: 225-292-1400  
 Fax: 225-292-1404

CLIENT \_\_\_\_\_ PROJECT NAME Peggy Lake Placement Area  
 PROJECT NUMBER W912HY-13-D-0001; Task Order 0002 PROJECT LOCATION La Porte, Texas

C:\DOCUMENTS AND SETTINGS\RL\KTO\PEGGY LAKE PLACEMENT AREA 3. 9-27-13.GPJ  
 C:\GEO TECH BH - PEGGY LAKE TEMPLATE.GDT - 10/2/13 10:39 - C:\DOCUMENTS AND SETTINGS\RL\KTO\PEGGY LAKE PLACEMENT AREA 3. 9-27-13.GPJ  
 COPY OF PEGGY

GRAPHIC LOG	USCS SYMBOL	MATERIAL DESCRIPTION	DEPTH (ft)	SAMPLE TYPE	RECOVERY (in)	SPT BLOW COUNTS (N VALUE)	POCKET PEN. (tsf)	FIELD TORVANE (tsf)	DRY UNIT WT. (pcf)	MOISTURE CONTENT (%)	ATTERBERG LIMITS				MINUS #200 SIEVE CONTENT (%)	COMPRESSIVE STRENGTH (tsf)	FAILURE STRAIN (%)	CONFINING PRESSURE (psi)	
											LIQUID LIMIT	PLASTIC LIMIT	PLASTICITY INDEX						
	CL	Silty CLAY, olive gray, moist, low plasticity, with shells (increasing with depth) and caliche (continued)	35	ST	13		0.3			43									
	CH	CLAY, yellow orange and light gray, slightly moist, medium to high plasticity, with caliche		ST	22		0/1.3	4.7/-		34									
	ML	Clayey SILT, light brown and light gray, slightly moist, low plasticity, with a little caliche laminations present	40	ST	22		1.5/1.5			21									
			ST	19		2.0/3.0		109	19										
		ST	20		2.5			18											
		ST	20	45		3.75/1.95			15										
		ST	20			>4.5/>4.5		115	16	39	15	24	85	2.27	2.9	0			
	CL	Silty CLAY, orange, slightly moist to slightly dry, medium plasticity, with iron/manganese oxide staining and nodules and caliche	50	ST	19		>4.5/4.0			16									
			ST	17		3.3/3.0			21										
		ST	11		>4.5			23											
		ST	14	55		>4.5			23										
		ST	18			4.25			24										
		with dry sections and black staining, looks baked, crumbly and hard sections		ST	19		3.9/2.6												

Bottom of borehole at 60.0 feet.