

LOCATION AND DEPTH OF BORINGS  
FOR  
ARANSAS PASS TRIBUTARY CHANNEL

22 September 1969

<u>Boring No.</u>	<u>Channel Station</u>	<u>Offset from Centerline</u>	<u>Water Depth</u>	<u>Boring Length Ft.</u>	<u>Boring Bottom Elevation</u>
3ST-1	0+00	75' R	12'	13'	-25'
3ST-2	10+00	75' L	15'	10'	-25'
3ST-3	20+00	75' R	15'	10'	-25'
3ST-4	30+00	75' L	14'	11'	-25'
3ST-5	40+00	75' R	12'	13'	-25'
3ST-6	50+00	75' L	13'	12'	-25'
3ST-7	60+00	75' R	14'	11'	-25'
3ST-8	70+00	75' L	14'	11'	-25'
3ST-9	80+00	75' R	13'	12'	-25'
3ST-10	90+00	75' L	12'	13'	-25'
3ST-11	100+00	75' R	13'	12'	-25'
3ST-12	110+00	75' L	14'	11'	-25'
3ST-13	120+00	75' R	13'	12'	-25'
3ST-14	130+00	75' L	15'	10'	-25'
3ST-15	140+00	75' R	14'	11'	-25'
3ST-16	150+00	75' L	16'	9'	-25'
3ST-17	160+00	75' R	14'	11'	-25'
3ST-18	170+00	75' L	15'	10'	-25'
3ST-19	180+00	75' R	13'	12'	-25'
3ST-20	190+00	75' L	8'	17'	-25'
3ST-21	200+00	75' R	12'	13'	-25'
3ST-22	210+00	75' L	8'	17'	-25'
3ST-23	220+00	75' R	7'	18'	-25'
3ST-24	230+00	75' L	12'	13'	-25'
3ST-25	240+00	75' R	9'	16'	-25'
3ST-26	250+00	75' L	9'	16'	-25'
3ST-27	260+00	75' R	9'	16'	-25'
3ST-28	270+00	75' L	9'	16'	-25'
3ST-29	280+00	75' R	10'	15'	-25'
3ST-30	290+00	75' L	10'	15'	-25'
3ST-31	300+00	75' R	9'	16'	-25'
3ST-32	310+00	75' L	11'	14'	-25'
3ST-33	320+00	75' R	12'	13'	-25'
3ST-34	-0+12*	Centerline	13'	12'	-25'
3ST-35	8+00*	150' R	13'	12'	-25'
3ST-36	16+00*	150' L	14'	11'	-25'
3ST-37	22+00*	150' R	14'	11'	-25'
3ST-38	29+00*	150' L	12'	13'	-25'

\*Aransas Pass Turning Basin stationing.

SW Form 267  
28 Jan 1965

*Right*

PROJECT: G.I.W.W., Tributary Channel

BORING NO. 35T-3

LOCATION: Aransas Pass

TEST DATA SUMMARY

DATE DRILLED Oct. 7, 1969

FIELD NO.	DEPTH	CLASSIFICATION ELEVATION TOP BORING _____	SYMBOL	CONSISTENCY	POCKET (1) PENETROMETER	STAN. PENET. BLOWS/FT (2)	MOISTURE CONTENT %	DRY DENSITY P. C. F.	L. L.	P. I.	BAR L. S.	SIEVE ANALYSIS								
												PERCENT			INIT. WT.	ACC. WT. RTND. SIEVE NO. (3)				
												GRVL	SAND	FINES		NO. 4	NO. 10	NO. 40	NO. 200	
	0-17.5	Water																		
J-1	17.5-20	Gray Sand	SP	VS	0.0	24														
J-2	20-22	Shell fragments		D		14	22				0.0	2	94	4	50	1	2	3	48	
X	22-25	Driller's classification: Same as Above.																		
J-3	25-27			VD		49	21													
		BOTTOM AT 27'																		
		WATER AT +17.5'																		
		Tide 2.0 @ 9:15 A.M.																		

KEY: CONSISTENCY - COHESIVE SOILS      CONSISTENCY - COHESIONLESS SOILS      (1) Tons/Sq. Ft. Unconfined Compressive Strength  
 VS S M ST VST H      VL L M D VD      (2) Split Barrel Sampler  
 Very Soft Soft Medium Stiff Very Stiff Hard      Very Loose Loose Medium Dense Very Dense      (3) Acc. Wt. Rtn'd ÷ Init. Wt. x 100 = % Rtn'd.

BORING NO. 35T-3